

Decotouch Wall Putty is a premium wall finishing product from the House of Decotouch. The wall putty is one among the several quality products the company has been producing in the wall finishing range. Decotouch has been a house-hold name in India for more than seven years now.

PRODUCT

Decotouch Wall Putty is a dry powder-based product to be used for overcoming the undulation on the surface of any plastered wall. The wall putty is a mixture of white cement, polymer, cellulose, pigments, if any, and many other additives required to improve its efficiency and performance.

ADVANTAGE

The object of using Decotouch Wall Putty is to give wall surface a smooth and even-look so that the top coat paint could give a maximum sheen finish and shine. It gives cost advantage as compared to the one on which no Decotouch Wall Putty is applied as the consumption of other wall finishing material comes down.

APPLICATION

Decotouch Wall Putty can be used internally as well as externally. It is recommended to apply Decotouch Wall Putty on a dry plastered surface. The Decotouch Wall Putty can be used on a new as well as on an old plastered surface. It can be applied on any mortar plastered/concrete surface in sound condition.

TECHNICAL DATA

Coverage per kg	Application by } Trowel/putty knife }	1st Coat 2nd Coat	1.5-2.0mm 2.0-2.5mm	9-10 Sq.Mtr 7-8 Sq.Mtr
Recommended Thinner	Potable Water			
Density (Dry Powder)	1.7 gm/cm ³			
Pot Life of Wet Paste	1 Hour			
Drying Time	SD : 45-60 minutes depending upon weather conditions; HD : 4-6 Hours (preferably overnight)			
Shelf Life	6 Months, if stored in cool and dry place.			
Flash Point	Since it is water-based product, FP is not applicable.			
Moisture content in wall Surface	Ideally, not more than 12%			
pH value of surface	Ideally, between 7-11			

DIRECTION FOR USE

Clean the surface from all loose sand/plaster, oil or any sticky material with sand paper (no.80/100). Apply one coat of Decotouch Wall Putty paste, made by mixing the putty powder with 45% (v/w) potable water. The thickness of the wall putty should not be more than 1.0mm in the first coat. Let the surface dry for 6-8 hours. After surface if touch-dry, apply second coat of Decotouch Wall Putty with 50% (v/w) mixing, on the first coat. The overall thickness of the putty layer must not exceed 2.0-2.5mm anywhere on the wall. The prepared surface should be left drying for 6-8 hours before applying primer/paint over it.

SAFETY

Decotouch Wall Putty is inflammable.

It is free from any heavy metal like lead, chromium and mercury which are harmful to the human.

PACKS AVAILABILITY

Decotouch Wall Putty is available in 40kg, 20kg, 5kg and 1kg packs. The pack size is subject to change without prior notice and for the availability of latest pack sizes, please contact the company.