



Wall Putty

Product Description : Decotouch Wall Putty for use on concrete/mortar (internal / external) and ceiling. It's filled the pores of concrete/mortar wall/ceiling and provide white smooth and dry surface. Decotouch Wall Putty has more adhesive strength. Durability and enhances the life of paints.

Performance Features :

- Curing not required.
- Applied on both interior/external surface.
- It prevents from algae and fungi on wall.
- Any kind of paint/distemper can be applied on it.
- It is a cementation material it has better adhesiveness and durability.
- No need to apply any kind of primer before application of paint/distemper.

Product Specifications

Area of Application : Concrete/Mortar Plaster (Interior & Exterior Walls).

Drying Time : Touch Dry: 30 Minutes
Re-coating interval: 3-4 hours

Thinner : Clean Water

Finish : Smooth & Matt.

Coverage : 2–2.75 m²/kg. /mm. in two coats.
However, the same may vary subject to the condition of the substrate.

Application : By Putty Blade or Steel Trowel

Wall Putty

- Clean up** : Wash equipments with clean water immediately after use.
- Shelf life** : Within 6 months from the date of manufacturing (Bag should be in original sealed condition).
- Packing** : 20 kg & 40 kg bags.
- Material Handling** : Decotouch wall putty shall be stored in a dry place away from moisture and rain.
- Technical data** : Tensile Adhesion strength : 23 kg/cm²
Compressive Strength at 28 days 180kg/cm²
- Surface Preparation** : Remove all dirt, loose particle, laitance from the surface with the help of emery stone paper, wire brush or putty- blade. Prior to application of Decotouch wall putty, it is very necessary that the surface should be properly wetted with clean water to ensure good adhesion besides better coverage and easy work ability.
- Mixing** : Mix wall putty with 30-35% clean water by a trowel or paddle type mixer (250-400 rpm) to a smooth- consistency. Mixing time shall be 10-15 minutes depending on the quantity of material and mixing method. For better result, keep mixing the material frequently during application. Only that much material shall be mixed with water as that can be consumed within 3 hours.
The pot life of mixed materials is three hours at 30C
- Application** : Freshly mixed wall putty should be applied on moist surface in a thin layer with the help of a putty blade or steel trowel. It is essential that the application is done from bottom to upwardly direction with the putty blade or steel trowel. Allow the surface to dry for at least 3-4 hour and apply the second coat as mentioned above. After dry of the second coat allow it to dry for 3-4 days before the application of paint. If required, treated surface can be sanded with 320 no. sand stone paper before application of paint. Maximum 2-3 coats can be applied but the thickness of each coat should not be more then 1mm. Generally, 1 to 1.5mm coating thickness is advisable for putty application.
- Precautions** : During extremely hot weather application finished coat shall be cured by sprinkling of water for 1-2 days for best results. Do not apply thick coat (more than 1-1.5mm) in one go.

Warranty : The information given in the technical data sheet is true and accurate. As workmanship, weather, quality of other materials and other variable affecting results are all beyond our control, Decotouch paints does not make nor does it authorize any agent or representative to make any warranty, guarantee or representation, expressed or implied concerning this product except that it confirms to Decotouch Paint's quality control standards. Any liability whatsoever of Decotouch Paints Limited, to the buyer or user of this product is limited to the purchaser's cost of the product itself.



Approved by :



Decotouch Paints Limited

Mob. : 730 2255 187

E-mail- sales@decotouchpaints.com, Website : www.decotouchpaints.com

